



no frame flex difusa sm r e

linha de luminárias embutidas para tecnologia led, para forro de gesso, parede ou piso, com opções de fachos fixos e orientáveis. sua principal característica é a fixação sem moldura, conferindo um acabamento limpo aos ambientes.

informações técnicas

fonte de luz
LED integrado

IRC
alto índice de reprodução de cor (irc>90|r9>60)


vida útil
50.000h

potência (W), facho, temperatura de cor (K),
fluxo nominal (lm nominal), fluxo útil (lm útil)

W		K	lm nominal	lm útil
6,5	d	2500		
6,5	d	2700		
6,5	d	3000	938	317
6,5	d	4000		
6	c	2700		
6	m	2700		
6	a	2700		
6	c	3000	690	431
6	m	3000	690	519
6	a	3000	690	448
12,5	c	2700		
12,5	m	2700		
12,5	a	2700		
12,5	c	3000	1550	1152
12,5	m	3000	1550	1096
12,5	a	3000	1550	1053
12,5	c	4000		
12,5	m	4000		
12,5	a	4000		

equipamentos
LED driver 180mA (incluso, ponto remoto)
LED driver 350mA (incluso, ponto remoto)

controle
0-10V
dim fphase
dim dali



acabamentos e cores

cores

cinza areia	branco txt
grafite txt	cinza médio
titânio	preto txt
corten	



no frame flex sm r e

linha de luminárias embutidas para tecnologia led, para forro de gesso, parede ou piso, com opções de facho fixos e orientáveis. sua principal característica é a fixação sem moldura, conferindo um acabamento limpo aos ambientes.

informações técnicas

fonte de luz
LED integrado

IRC
alto índice de reprodução de cor (irc>90 | r9>60)

vida útil
50.000h

potência (W), facho, temperatura de cor (K),
fluxo nominal (lm nominal), fluxo útil (lm útil)

W		K	lm nominal	lm útil
6,5	d	2500		
6,5	d	2700		
6,5	d	3000	938	317
6,5	d	4000		
6	c	2700		
6	m	2700		
6	a	2700		
6	c	3000	690	431
6	m	3000	690	519
6	a	3000	690	448
12,5	c	2700		
12,5	m	2700		
12,5	a	2700		
12,5	c	3000	1550	1152
12,5	m	3000	1550	1096
12,5	a	3000	1550	1053
12,5	c	4000		
12,5	m	4000		
12,5	a	4000		
12	c	dim to warm	924	651
12	m	dim to warm	924	649
12	a	dim to warm	924	631


equipamentos
LED driver 180mA (incluso, ponto remoto)
LED driver 350mA (incluso, ponto remoto)
LED driver 700mA (incluso, ponto remoto)

controle
on/off
dim fphase
dim dali
dim 1-10V

instalação
forro de gesso

IP
20

dimensões





acabamentos e cores

cores



vista lateral

dimensões em milímetros



no frame flex difusa
sm r série 2 e

folha
1/1

escala
1:2


data
07/04/2020

desenhista
joao ferreira

aprovação
edmilson


revisões

09/04/2020



vista inferior

dimensões em milímetros



para maiores informações,
consulte a área técnica
produto@lumini.com.br



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email: laboratorio@lumini.com.br
Tel: +55 11 3437-5555 Fax: +55 11 3437-5555
Address: Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex difusa sm r serie 2 e

LampCAT: modulo led 6.5W 30K irc 90

Ballast type: led driver 700mA

Report No:

Voltage(V): 127.9100

Test No:

Current(A): 0.0640

Number of Lamps: 1

Power (W): 7.7730

Lamp flux(lm): 938.0

PF: 0.9540

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 316.85, Efficiency(%): 33.78% , Luminous Efficacy(lm/W): 40.76

Central intensity(cd): 216.911, Maximum intensity(cd): 216.911

Angle of maximum intensity: $C=0.0$ $\gamma=0.0$


Beam angle of C0 plane : 74.58


Average BeamAngle(IEC 61341): 74.58

Equipment: equipamento lumini
Temperature(°C): 25.0


Date: 02/06/2025
Humidity(%): 58.0%

Operator: 01
Distance(m): 6.90





Max , Ave Beam angle of C0 plane 74.58



Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	31723	22673	14241	7236	3235	1841	1779	1994	3115
C45	31723	22673	14241	7236	3235	1841	1779	1994	3115
C90	31723	22673	14241	7236	3235	1841	1779	1994	3115

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
3235	3235	3235	1779	1779	1779	3115	3115	3115

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

 $\gamma(^{\circ})$ 

C0 ———

C45 ———

C90 ———

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	22.21	23.42	22.60	23.77	24.13	22.60	23.81	22.99	24.16	24.52
	3H	22.09	23.16	22.50	23.53	23.92	22.49	23.56	22.91	23.94	24.32
	4H	22.02	23.01	22.44	23.40	23.80	22.42	23.41	22.85	23.80	24.21
	6H	21.96	22.87	22.40	23.28	23.72	22.37	23.28	22.81	23.68	24.12
	8H	21.90	22.77	22.35	23.19	23.64	22.31	23.18	22.75	23.59	24.04
	12H	21.85	22.68	22.30	23.10	23.56	22.26	23.08	22.71	23.51	23.97
4H	2H	22.17	23.16	22.60	23.55	23.96	22.53	23.52	22.96	23.91	24.32
	3H	22.03	22.85	22.49	23.28	23.73	22.41	23.23	22.86	23.65	24.11
	4H	22.00	22.71	22.47	23.16	23.65	22.38	23.09	22.84	23.54	24.03
	6H	21.90	22.53	22.40	23.01	23.50	22.28	22.91	22.78	23.39	23.88
	8H	21.87	22.45	22.38	22.94	23.44	22.24	22.83	22.75	23.31	23.82
	12H	21.84	22.38	22.36	22.86	23.42	22.22	22.76	22.74	23.24	23.79
8H	4H	21.84	22.42	22.35	22.91	23.42	22.21	22.80	22.72	23.28	23.79
	6H	21.73	22.22	22.26	22.72	23.27	22.11	22.59	22.64	23.10	23.65
	8H	21.75	22.17	22.30	22.72	23.25	22.12	22.54	22.68	23.09	23.62
	12H	21.73	22.08	22.29	22.62	23.18	22.11	22.45	22.67	23.00	23.55
12H	4H	21.80	22.33	22.31	22.81	23.37	22.17	22.71	22.68	23.19	23.74
	6H	21.73	22.15	22.28	22.69	23.23	22.10	22.52	22.66	23.07	23.60
	8H	21.71	22.05	22.27	22.60	23.15	22.08	22.43	22.64	22.97	23.52
Variation with the observer position at spacings:											
S = 1.0H		1.1/-3.0					1.1/-3.0				
S = 1.5H		2.8/-7.7					2.8/-7.7				
S = 2.0H		5.5/-9.8					5.5/-9.8				
Standard tables:		BK0					BK0				
Uncorrected UGR		2.6					2.6				

依据CIE Publ. 117 计算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email: laboratorio@lumini.com.br
Tel: +55 11 3437-5555 Fax: +55 11 3437-5555
Address: Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r cob serie 3 e fc

LampCAT: modulo led 6W 3000K irc 90

Ballast type: led driver 180mA

Report No:

Voltage(V): 127.0000

Test No:

Current(A): 0.0610

Number of Lamps: 1

Power (W): 7.6500

Lamp flux(lm): 690.0

PF: 0.9900

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 431.09, Efficiency(%): 62.48% , Luminous Efficacy(lm/W): 56.35

Central intensity(cd): 2087.448, Maximum intensity(cd): 2087.448

Angle of maximum intensity: $C=0.0$ $\gamma=0.0$


Beam angle of C0 plane : 21.80


Average BeamAngle(IEC 61341): 21.80

Equipment: equipamento lumini
Temperature(°C): 25.5


Date: 5/14/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90





Max , Ave Beam angle of C0 plane 21.80



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:6

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	9549	7339	5248	3282	1927	1369	1581	2266	4334
C45	9549	7339	5248	3282	1927	1369	1581	2266	4334
C90	9549	7339	5248	3282	1927	1369	1581	2266	4334


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
1927	1927	1927	1581	1581	1581	4334	4334	4334

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 ———

C45 ———

C90 ———

Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.5

Date: 5/14/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	14.01	14.99	14.38	15.30	15.62	13.22	14.19	13.58	14.50	14.82
	3H	13.96	14.83	14.35	15.17	15.51	13.19	14.06	13.58	14.39	14.74
	4H	13.93	14.73	14.33	15.09	15.46	13.18	13.98	13.58	14.34	14.71
	6H	13.98	14.71	14.40	15.09	15.49	13.26	13.99	13.68	14.37	14.77
	8H	14.01	14.71	14.43	15.09	15.50	13.32	14.02	13.74	14.40	14.81
	12H	14.13	14.79	14.55	15.18	15.60	13.45	14.11	13.88	14.51	14.93
4H	2H	13.98	14.78	14.38	15.14	15.50	13.26	14.06	13.66	14.42	14.78
	3H	13.94	14.61	14.36	15.00	15.42	13.25	13.92	13.68	14.31	14.73
	4H	13.98	14.56	14.42	14.98	15.43	13.32	13.90	13.76	14.32	14.77
	6H	14.05	14.56	14.53	15.02	15.47	13.44	13.95	13.91	14.40	14.86
	8H	14.17	14.64	14.66	15.10	15.58	13.59	14.06	14.08	14.52	15.00
	12H	14.42	14.86	14.91	15.31	15.83	13.87	14.30	14.36	14.75	15.27
8H	4H	13.86	14.33	14.35	14.79	15.26	13.22	13.69	13.71	14.15	14.63
	6H	14.02	14.41	14.53	14.89	15.40	13.45	13.83	13.95	14.31	14.83
	8H	14.29	14.61	14.82	15.13	15.63	13.76	14.08	14.29	14.60	15.10
	12H	14.71	14.96	15.25	15.48	16.00	14.21	14.46	14.76	14.98	15.50
12H	4H	13.83	14.27	14.32	14.72	15.24	13.20	13.63	13.69	14.09	14.61
	6H	14.07	14.40	14.61	14.92	15.42	13.51	13.83	14.04	14.36	14.85
	8H	14.35	14.60	14.89	15.12	15.64	13.84	14.09	14.38	14.61	15.13
Variation with the observer position at spacings:											
S = 1.0H		1.2/-2.0					1.2/-2.0				
S = 1.5H		2.5/-3.9					2.5/-3.9				
S = 2.0H		4.7/-4.1					4.7/-4.1				
Standard tables:		BK2					BK2				
Uncorrected UGR		-4.7					-4.7				

依据CIE Publ. 117 计算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r cob serie 3 e fm

LampCAT: modulo led 6W 3000K irc 90

Ballast type: led driver 180mA

Report No:

Voltage(V): 127.0000

Test No:

Current(A): 0.0600

Number of Lamps: 1

Power (W): 7.6600

Lamp flux(lm): 690.0

PF: 0.9900

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 518.75, Efficiency(%): 75.18% , Luminous Efficacy(lm/W): 67.72

Central intensity(cd): 1645.592, Maximum intensity(cd): 1645.592

Angle of maximum intensity: $C=0.0$ $\gamma=0.0$


Beam angle of C0 plane : 27.56


Aveage BeamAngle(IEC 61341):27.56

Equipment: equipamento lumini
Temperature(°C): 25.5


Date: 5/15/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90





Max , Ave Beam angle of C0 plane 27.56



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:6

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	9404	6134	4174	2778	1741	1473	1779	2560	4876
C45	9404	6134	4174	2778	1741	1473	1779	2560	4876
C90	9404	6134	4174	2778	1741	1473	1779	2560	4876


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
1741	1741	1741	1779	1779	1779	4876	4876	4876

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 ———

C45 ———

C90 ———

Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.5

Date: 5/15/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	15.71	16.66	16.07	16.97	17.29	14.61	15.57	14.98	15.88	16.20
	3H	15.57	16.42	15.95	16.75	17.10	14.51	15.36	14.90	15.70	16.04
	4H	15.51	16.29	15.91	16.65	17.02	14.48	15.26	14.88	15.61	15.98
	6H	15.51	16.22	15.93	16.60	17.00	14.52	15.23	14.93	15.61	16.01
	8H	15.51	16.19	15.93	16.58	16.98	14.54	15.23	14.96	15.61	16.02
	12H	15.55	16.20	15.98	16.59	17.01	14.63	15.27	15.05	15.67	16.09
4H	2H	15.51	16.29	15.91	16.65	17.01	14.47	15.25	14.87	15.61	15.97
	3H	15.36	16.02	15.79	16.41	16.83	14.37	15.03	14.80	15.42	15.84
	4H	15.37	15.93	15.80	16.36	16.80	14.40	14.97	14.84	15.39	15.84
	6H	15.37	15.87	15.85	16.33	16.78	14.48	14.98	14.95	15.43	15.88
	8H	15.44	15.91	15.93	16.37	16.84	14.59	15.05	15.08	15.51	15.99
	12H	15.60	16.02	16.09	16.48	17.00	14.80	15.23	15.29	15.68	16.20
8H	4H	15.22	15.68	15.70	16.14	16.61	14.28	14.74	14.76	15.20	15.67
	6H	15.29	15.67	15.80	16.15	16.66	14.44	14.81	14.94	15.29	15.81
	8H	15.48	15.80	16.02	16.32	16.82	14.69	15.01	15.23	15.53	16.03
	12H	15.77	16.01	16.31	16.53	17.05	15.06	15.30	15.60	15.82	16.34
12H	4H	15.18	15.61	15.67	16.06	16.58	14.25	14.67	14.74	15.12	15.65
	6H	15.32	15.64	15.86	16.16	16.66	14.49	14.80	15.02	15.33	15.82
	8H	15.52	15.77	16.07	16.28	16.81	14.76	15.00	15.30	15.52	16.04
Variation with the observer position at spacings:											
S = 1.0H		3.7/-4.1					3.7/-4.1				
S = 1.5H		5.9/-4.9					5.9/-4.9				
S = 2.0H		7.5/-4.5					7.5/-4.5				
Standard tables:		BK2					BK2				
Uncorrected UGR		-4.2					-4.2				

依据CIE Publ. 117 计算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email: laboratorio@lumini.com.br
Tel: +55 11 3437-5555 Fax: +55 11 3437-5555
Address: Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r cob serie 3 e fa

LampCAT: modulo led 6W 3000K irc 90

Ballast type: led driver 180mA

Report No:

Voltage(V): 127.0000

Test No:

Current(A): 0.0610

Number of Lamps: 1

Power (W): 7.6500

Lamp flux(lm): 690.0

PF: 0.9900

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 447.93, Efficiency(%): 64.92% , Luminous Efficacy(lm/W): 58.55

Central intensity(cd): 756.202, Maximum intensity(cd): 756.202

Angle of maximum intensity: $C=0.0$ $\gamma=0.0$



Beam angle of C0 plane : 43.15

Average BeamAngle(IEC 61341): 43.15


Equipment: equipamento lumini
Temperature(°C): 25.5

Date: 5/14/2024
Humidity(%): 55.0%


Operator: 01
Distance(m): 6.90



C0(Max): —————
 C0/C180: —————
 C90/C270: —————



Max , Ave Beam angle of C0 plane 43.15



Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	12186	8178	5399	3238	1755	1358	1573	2198	3973
C45	12186	8178	5399	3238	1755	1358	1573	2198	3973
C90	12186	8178	5399	3238	1755	1358	1573	2198	3973

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
1755	1755	1755	1573	1573	1573	3973	3973	3973

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

 $\gamma(^{\circ})$ 

C0 ———

C45 ———

C90 ———

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	17.34	18.33	17.70	18.64	18.95	16.27	17.26	16.63	17.57	17.88
	3H	17.18	18.06	17.57	18.40	18.74	16.13	17.01	16.52	17.35	17.69
	4H	17.11	17.92	17.51	18.27	18.64	16.07	16.88	16.47	17.23	17.60
	6H	17.08	17.82	17.49	18.19	18.59	16.05	16.79	16.47	17.17	17.57
	8H	17.04	17.75	17.47	18.14	18.54	16.03	16.74	16.45	17.12	17.53
	12H	17.03	17.70	17.46	18.10	18.52	16.04	16.71	16.47	17.11	17.53
4H	2H	17.13	17.94	17.53	18.30	18.67	16.11	16.92	16.51	17.27	17.64
	3H	16.97	17.64	17.39	18.04	18.45	15.97	16.64	16.39	17.04	17.46
	4H	16.94	17.52	17.37	17.94	18.39	15.96	16.54	16.39	16.96	17.41
	6H	16.89	17.40	17.36	17.86	18.31	15.93	16.45	16.41	16.90	17.35
	8H	16.91	17.38	17.39	17.84	18.32	15.97	16.45	16.46	16.91	17.38
	12H	16.97	17.41	17.46	17.86	18.38	16.07	16.50	16.56	16.96	17.48
8H	4H	16.77	17.24	17.25	17.70	18.18	15.80	16.28	16.29	16.74	17.21
	6H	16.76	17.15	17.26	17.63	18.14	15.82	16.21	16.33	16.69	17.21
	8H	16.86	17.19	17.40	17.71	18.21	15.97	16.29	16.50	16.82	17.31
	12H	16.99	17.25	17.54	17.77	18.29	16.15	16.40	16.69	16.92	17.44
12H	4H	16.73	17.17	17.22	17.62	18.14	15.76	16.20	16.25	16.65	17.17
	6H	16.77	17.10	17.30	17.62	18.12	15.85	16.17	16.38	16.70	17.19
	8H	16.86	17.12	17.40	17.63	18.16	15.98	16.23	16.52	16.75	17.27
Variation with the observer position at spacings:											
S = 1.0H		3.7/-4.5					3.7/-4.5				
S = 1.5H		6.0/-6.5					6.0/-6.5				
S = 2.0H		8.0/-6.4					8.0/-6.4				
Standard tables:		BK1					BK1				
Uncorrected UGR		-2.8					-2.8				

依据CIE Publ. 117 计算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r serie 2 cob fc

LampCAT: modulo led 12.5W 3000K irc 90

Ballast type: led driver 350mA

Report No:

Voltage(V): 127.0000

Test No:

Current(A): 0.1100

Number of Lamps: 1

Power (W): 13.7400

Lamp flux(lm): 1550.0

PF: 0.9800

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 1152.05, Efficiency(%): 74.33% , Luminous Efficacy(lm/W): 83.85

Central intensity(cd): 4858.219, Maximum intensity(cd): 4858.219

Angle of maximum intensity: C=0.0 γ =0.0


Beam angle of C0 plane : 23.24


Aveage BeamAngle(IEC 61341):23.24

Equipment: equipamento lumini
Temperature(°C): 25.5


Date: 5/9/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90





Max , Ave Beam angle of C0 plane 23.24



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:6

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	9588	7695	6538	5642	4567	3630	4051	5755	10970
C45	9588	7695	6538	5642	4567	3630	4051	5755	10970
C90	9588	7695	6538	5642	4567	3630	4051	5755	10970


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
4567	4567	4567	4051	4051	4051	10970	10970	10970

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 ———

C45 ———

C90 ———

Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.5

Date: 5/9/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	13.69	14.62	14.05	14.93	15.25	13.76	14.69	14.12	15.00	15.32
	3H	13.92	14.75	14.31	15.09	15.43	13.94	14.77	14.33	15.10	15.45
	4H	14.02	14.78	14.42	15.13	15.50	14.03	14.79	14.43	15.14	15.51
	6H	14.25	14.95	14.67	15.32	15.72	14.25	14.94	14.67	15.32	15.72
	8H	14.43	15.10	14.86	15.48	15.89	14.43	15.09	14.85	15.48	15.89
	12H	14.73	15.36	15.16	15.75	16.17	14.72	15.35	15.15	15.75	16.17
4H	2H	13.66	14.42	14.06	14.78	15.15	13.73	14.49	14.13	14.84	15.21
	3H	13.98	14.61	14.40	15.01	15.43	13.99	14.63	14.41	15.02	15.44
	4H	14.20	14.75	14.64	15.17	15.62	14.20	14.75	14.64	15.17	15.62
	6H	14.55	15.04	15.03	15.49	15.95	14.54	15.02	15.01	15.48	15.93
	8H	14.88	15.33	15.37	15.79	16.27	14.87	15.32	15.35	15.78	16.25
	12H	15.38	15.79	15.87	16.24	16.77	15.36	15.78	15.85	16.23	16.75
8H	4H	14.19	14.64	14.68	15.10	15.57	14.19	14.64	14.68	15.10	15.57
	6H	14.73	15.10	15.24	15.58	16.09	14.72	15.09	15.23	15.57	16.08
	8H	15.28	15.59	15.82	16.11	16.61	15.27	15.57	15.80	16.10	16.60
	12H	16.02	16.25	16.57	16.77	17.30	16.01	16.24	16.55	16.76	17.28
12H	4H	14.19	14.61	14.68	15.06	15.58	14.19	14.61	14.68	15.06	15.58
	6H	14.86	15.16	15.39	15.69	16.18	14.84	15.15	15.38	15.67	16.17
	8H	15.46	15.69	16.01	16.21	16.74	15.45	15.68	15.99	16.20	16.72
Variation with the observer position at spacings:											
S = 1.0H		3.2/-1.9					3.2/-1.9				
S = 1.5H		4.6/-2.1					4.6/-2.1				
S = 2.0H		5.7/-2.0					5.7/-2.0				
Standard tables:		BK4					BK4				
Uncorrected UGR		-3.4					-3.4				

依据CIE Publ. 117 计算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email: laboratorio@lumini.com.br
Tel: +55 11 3437-5555 Fax: +55 11 3437-5555
Address: Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r serie 2 cob fm

LampCAT: modulo led 12.5W 3000K irc 90

Ballast type: led driver 350mA

Report No:

Voltage(V): 127.0000

Test No:

Current(A): 0.1100

Number of Lamps: 1

Power (W): 13.7400

Lamp flux(lm): 1550.0

PF: 0.9800

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 1095.57, Efficiency(%): 70.68% , Luminous Efficacy(lm/W): 79.74

Central intensity(cd): 3759.762, Maximum intensity(cd): 3759.762

Angle of maximum intensity: $C=0.0$ $\gamma=0.0$


Beam angle of C0 plane : 27.65


Average BeamAngle(IEC 61341): 27.65

Equipment: equipamento lumini
Temperature(°C): 25.5


Date: 5/9/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90





Max , Ave Beam angle of C0 plane 27.65



Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	0	8359	0	5733	0	3572	0	5529	0
C45	0	8359	0	5733	0	3572	0	5529	0
C90	0	8359	0	5733	0	3572	0	5529	0

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
4567	4567	4567	4051	4051	4051	10970	10970	10970

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

 $\gamma(^{\circ})$ 

C0 ———

C45 ———

C90 ———

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	14.44	15.37	14.80	15.68	16.00	14.49	15.42	14.85	15.73	16.05
	3H	14.59	15.42	14.98	15.76	16.11	14.65	15.48	15.03	15.81	16.16
	4H	14.64	15.41	15.05	15.77	16.13	14.70	15.46	15.10	15.82	16.19
	6H	14.83	15.53	15.24	15.90	16.30	14.87	15.57	15.29	15.95	16.35
	8H	14.97	15.63	15.39	16.02	16.43	15.01	15.68	15.43	16.06	16.47
	12H	15.20	15.83	15.63	16.23	16.64	15.24	15.87	15.67	16.27	16.69
4H	2H	14.39	15.16	14.79	15.51	15.88	14.44	15.21	14.84	15.56	15.93
	3H	14.61	15.25	15.04	15.65	16.07	14.66	15.30	15.08	15.70	16.11
	4H	14.77	15.33	15.21	15.75	16.20	14.82	15.37	15.26	15.80	16.25
	6H	15.05	15.54	15.53	16.00	16.45	15.09	15.58	15.57	16.04	16.49
	8H	15.33	15.78	15.82	16.24	16.72	15.37	15.82	15.85	16.28	16.75
	12H	15.74	16.16	16.23	16.61	17.13	15.78	16.19	16.27	16.65	17.17
8H	4H	14.73	15.19	15.22	15.65	16.12	14.78	15.23	15.27	15.69	16.17
	6H	15.18	15.55	15.69	16.03	16.54	15.22	15.59	15.72	16.07	16.58
	8H	15.66	15.97	16.19	16.49	16.99	15.69	16.00	16.22	16.52	17.02
	12H	16.29	16.53	16.84	17.05	17.57	16.32	16.56	16.87	17.07	17.60
12H	4H	14.73	15.15	15.22	15.60	16.12	14.77	15.19	15.27	15.64	16.17
	6H	15.29	15.59	15.82	16.12	16.62	15.32	15.63	15.86	16.15	16.65
	8H	15.81	16.04	16.35	16.56	17.08	15.83	16.07	16.38	16.59	17.11
Variation with the observer position at spacings:											
S = 1.0H		3.4/-2.2					3.4/-2.2				
S = 1.5H		5.0/-2.3					5.0/-2.3				
S = 2.0H		6.3/-2.3					6.3/-2.3				
Standard tables:		BK3					BK3				
Uncorrected UGR		-3.4					-3.4				

依据CIE Publ. 117 计算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r serie 2 cob fa

LampCAT: modulo led 12.5W 3000K irc 90

Ballast type: led driver 350mA

Report No:

Voltage(V): 127.0000

Test No:

Current(A): 0.1100

Number of Lamps: 1

Power (W): 13.7400

Lamp flux(lm): 1550.0

PF: 0.9800

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 1052.53, Efficiency(%): 67.91% , Luminous Efficacy(lm/W): 76.60

Central intensity(cd): 2427.491, Maximum intensity(cd): 2427.491

Angle of maximum intensity: C=0.0 γ =0.0


Beam angle of C0 plane : 38.07


Aveage BeamAngle(IEC 61341):38.07

Equipment: equipamento lumini
Temperature(°C): 25.5

Date: 5/9/2024
Humidity(%): 55.0%


Operator: 01
Distance(m): 6.90





Max , Ave

Beam angle of C0 plane 38.07



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:6

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	12687	9727	7666	5985	4571	3503	3747	5246	10068
C45	12687	9727	7666	5985	4571	3503	3747	5246	10068
C90	12687	9727	7666	5985	4571	3503	3747	5246	10068


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
4571	4571	4571	3747	3747	3747	10068	10068	10068

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 —

C45 —

C90 —

Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.5

Date: 5/9/2024
Humidity(%): 55.0%

Operator: 01
Distance(m): 6.90

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	16.60	17.55	16.97	17.86	18.17	15.43	16.37	15.79	16.68	17.00
	3H	16.64	17.48	17.03	17.82	18.16	15.46	16.29	15.84	16.63	16.98
	4H	16.63	17.40	17.03	17.76	18.13	15.46	16.24	15.87	16.59	16.96
	6H	16.69	17.40	17.11	17.77	18.17	15.57	16.28	15.99	16.66	17.06
	8H	16.73	17.41	17.16	17.79	18.20	15.65	16.33	16.08	16.71	17.12
	12H	16.84	17.48	17.27	17.87	18.29	15.81	16.45	16.24	16.85	17.27
4H	2H	16.45	17.22	16.85	17.58	17.95	15.34	16.12	15.74	16.47	16.84
	3H	16.52	17.17	16.95	17.56	17.98	15.41	16.06	15.84	16.46	16.88
	4H	16.59	17.15	17.03	17.57	18.02	15.52	16.07	15.95	16.50	16.95
	6H	16.69	17.19	17.17	17.64	18.09	15.69	16.19	16.17	16.64	17.09
	8H	16.83	17.29	17.32	17.75	18.22	15.89	16.34	16.37	16.80	17.28
	12H	17.08	17.50	17.57	17.95	18.47	16.20	16.62	16.70	17.08	17.60
8H	4H	16.48	16.93	16.97	17.39	17.87	15.44	15.90	15.93	16.36	16.83
	6H	16.68	17.06	17.19	17.54	18.05	15.75	16.12	16.26	16.60	17.12
	8H	16.98	17.29	17.51	17.81	18.31	16.12	16.43	16.66	16.95	17.45
	12H	17.39	17.63	17.94	18.15	18.67	16.64	16.88	17.18	17.39	17.92
12H	4H	16.45	16.87	16.94	17.33	17.85	15.43	15.85	15.92	16.30	16.82
	6H	16.74	17.05	17.28	17.58	18.07	15.83	16.14	16.37	16.67	17.16
	8H	17.06	17.29	17.60	17.81	18.33	16.24	16.47	16.78	16.99	17.51
Variation with the observer position at spacings:											
S = 1.0H		3.8/-2.8					3.8/-2.8				
S = 1.5H		5.7/-3.1					5.7/-3.1				
S = 2.0H		7.2/-3.0					7.2/-3.0				
Standard tables:		BK3					BK3				
Uncorrected UGR		-2.6					-2.6				

依据CIE Publ. 117 计算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r dtw e fc

LampCAT: modulo led dtw 12W 27K irc 90

Ballast type: led driver 700mA

Report No:

Voltage(V): 127.7800

Test No:

Current(A): 0.1130

Number of Lamps: 1

Power (W): 14.1220

Lamp flux(lm): 924.0

PF: 0.9760

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 650.56, Efficiency(%): 70.41% , Luminous Efficacy(lm/W): 46.07

Central intensity(cd): 3030.769, Maximum intensity(cd): 3030.769

Angle of maximum intensity: C=0.0 γ =0.0



Beam angle of C0 plane : 22.69

Aveage BeamAngle(IEC 61341):22.69


Equipment: equipamento lumini
Temperature(°C): 25.0

Date: 29/05/2025
Humidity(%): 58.0%


Operator: 01
Distance(m): 6.90



C0(Max):
C0/C180:
C90/C270:



Max , Ave Beam angle of C0 plane 22.69



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:6

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	3411	2831	2813	2829	2705	2318	2896	4056	7788
C45	3411	2831	2813	2829	2705	2318	2896	4056	7788
C90	3411	2831	2813	2829	2705	2318	2896	4056	7788


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
2705	2705	2705	2896	2896	2896	7788	7788	7788

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 ———

C45 ———

C90 ———

Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.0

Date: 29/05/2025
Humidity(%): 58.0%

Operator: 01
Distance(m): 6.90

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	7.09	7.99	7.50	8.35	8.72	7.43	8.33	7.83	8.68	9.05
	3H	8.19	9.00	8.62	9.38	9.78	8.59	9.39	9.02	9.77	10.17
	4H	8.86	9.60	9.30	10.00	10.42	9.18	9.92	9.62	10.32	10.74
	6H	9.90	10.58	10.36	11.00	11.45	10.12	10.80	10.58	11.22	11.67
	8H	10.55	11.20	11.01	11.62	12.08	10.70	11.35	11.16	11.78	12.24
	12H	11.40	12.01	11.87	12.45	12.92	11.47	12.08	11.94	12.52	12.99
4H	2H	7.56	8.31	8.01	8.70	9.12	7.84	8.58	8.28	8.98	9.40
	3H	8.82	9.45	9.29	9.88	10.35	9.13	9.76	9.60	10.20	10.67
	4H	9.73	10.27	10.20	10.73	11.23	9.97	10.50	10.44	10.97	11.47
	6H	10.97	11.44	11.48	11.94	12.44	11.11	11.59	11.62	12.08	12.58
	8H	11.78	12.22	12.30	12.72	13.24	11.87	12.31	12.39	12.80	13.33
	12H	12.82	13.23	13.35	13.72	14.29	12.83	13.23	13.36	13.72	14.29
8H	4H	10.06	10.50	10.58	11.00	11.52	10.27	10.71	10.79	11.20	11.73
	6H	11.61	11.97	12.15	12.48	13.05	11.71	12.07	12.26	12.59	13.15
	8H	12.68	12.98	13.25	13.54	14.08	12.73	13.03	13.30	13.59	14.13
	12H	13.99	14.21	14.57	14.77	15.34	13.96	14.19	14.54	14.74	15.31
12H	4H	10.16	10.57	10.69	11.06	11.63	10.36	10.77	10.89	11.26	11.83
	6H	11.87	12.17	12.44	12.73	13.28	11.97	12.27	12.54	12.83	13.38
	8H	13.02	13.25	13.60	13.80	14.37	13.06	13.29	13.64	13.85	14.42
Variation with the observer position at spacings:											
S = 1.0H		1.0/-0.9					1.0/-0.9				
S = 1.5H		1.2/-1.2					1.2/-1.2				
S = 2.0H		1.4/-0.9					1.4/-0.9				
Standard tables:		BKBF					BKBF				
Uncorrected UGR		-3.8					-3.8				

依据CIE Publ. 117 □算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r dtw e fm

LampCAT: modulo led dtw 12W 27K irc 90

Ballast type: led driver 700mA

Report No:

Voltage(V): 127.7900

Test No:

Current(A): 0.1140

Number of Lamps: 1

Power (W): 14.1610

Lamp flux(lm): 924.0

PF: 0.9760

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 649.02, Efficiency(%): 70.24% , Luminous Efficacy(lm/W): 45.83

Central intensity(cd): 2982.635, Maximum intensity(cd): 2982.635

Angle of maximum intensity: C=0.0 γ =0.0



Beam angle of C0 plane : 22.77

Aveage BeamAngle(IEC 61341):22.77


Equipment: equipamento lumini
Temperature(°C): 25.0

Date: 29/05/2025
Humidity(%): 58.0%


Operator: 01
Distance(m): 6.90



C0(Max):
C0/C180:
C90/C270:



Max , Ave Beam angle of C0 plane 22.77



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:6

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	3417	2834	2778	2790	2681	2347	2866	4101	7788
C45	3417	2834	2778	2790	2681	2347	2866	4101	7788
C90	3417	2834	2778	2790	2681	2347	2866	4101	7788


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
2681	2681	2681	2866	2866	2866	7788	7788	7788

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 ———

C45 ———

C90 ———

Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.0

Date: 29/05/2025
Humidity(%): 58.0%

Operator: 01
Distance(m): 6.90

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	6.80	7.70	7.21	8.06	8.43	7.22	8.12	7.62	8.47	8.84
	3H	7.91	8.71	8.33	9.09	9.49	8.34	9.14	8.77	9.52	9.92
	4H	8.61	9.36	9.05	9.75	10.17	8.96	9.71	9.41	10.10	10.53
	6H	9.67	10.34	10.13	10.77	11.22	9.93	10.60	10.38	11.02	11.48
	8H	10.32	10.97	10.78	11.39	11.85	10.55	11.19	11.01	11.62	12.08
	12H	11.15	11.76	11.61	12.20	12.67	11.35	11.96	11.82	12.40	12.87
4H	2H	7.25	7.99	7.69	8.39	8.81	7.59	8.33	8.03	8.73	9.15
	3H	8.53	9.15	8.99	9.59	10.06	8.87	9.50	9.34	9.94	10.40
	4H	9.49	10.02	9.96	10.49	10.99	9.75	10.29	10.23	10.75	11.25
	6H	10.75	11.22	11.26	11.72	12.22	10.93	11.41	11.44	11.90	12.40
	8H	11.57	12.01	12.09	12.51	13.03	11.73	12.17	12.25	12.67	13.19
	12H	12.58	12.99	13.11	13.48	14.05	12.73	13.13	13.26	13.63	14.19
8H	4H	9.85	10.29	10.37	10.79	11.31	10.07	10.51	10.59	11.01	11.53
	6H	11.42	11.78	11.96	12.30	12.86	11.57	11.93	12.11	12.44	13.00
	8H	12.51	12.81	13.08	13.37	13.91	12.63	12.93	13.20	13.49	14.04
	12H	13.78	14.01	14.36	14.56	15.13	13.90	14.12	14.47	14.68	15.25
12H	4H	9.96	10.37	10.49	10.86	11.43	10.17	10.58	10.70	11.07	11.64
	6H	11.70	12.00	12.27	12.56	13.11	11.84	12.13	12.41	12.69	13.24
	8H	12.87	13.10	13.45	13.65	14.22	12.98	13.21	13.56	13.76	14.33
Variation with the observer position at spacings:											
S = 1.0H		1.0/-0.9					1.0/-0.9				
S = 1.5H		1.2/-1.2					1.2/-1.2				
S = 2.0H		1.4/-0.9					1.4/-0.9				
Standard tables:		BKBF					BKBF				
Uncorrected UGR		-3.8					-3.8				

依据 CIE Publ. 117 □ 算 UGR, S/H = 0.25



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: no frame flex sm r dtw e fa

LampCAT: modulo led dtw 12W 27K irc 90

Ballast type: led driver 700mA

Report No:

Voltage(V): 127.7900

Test No:

Current(A): 0.1130

Number of Lamps: 1

Power (W): 14.1510

Lamp flux(lm): 924.0

PF: 0.9760

Length(mm): 55

Width(mm): 55

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 631.32, Efficiency(%): 68.32% , Luminous Efficacy(lm/W): 44.61

Central intensity(cd): 1533.506, Maximum intensity(cd): 1533.923

Angle of maximum intensity: C=0.0 γ =1.0


Beam angle of C0 plane : 38.01


Aveage BeamAngle(IEC 61341):38.01

Equipment: equipamento lumini
Temperature(°C): 25.0


Date: 29/05/2025
Humidity(%): 58.0%

Operator: 01
Distance(m): 6.90





Max , Ave Beam angle of C0 plane 38.01



Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	4463	3578	3025	2758	2616	2238	2721	3841	7246
C45	4463	3578	3025	2758	2616	2238	2721	3841	7246
C90	4463	3578	3025	2758	2616	2238	2721	3841	7246

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
2616	2616	2616	2721	2721	2721	7246	7246	7246

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

 $\gamma(^{\circ})$ 

C0 ———

C45 ———


C90 ———

Illumination assessment according UGR											
Rf of Ceiling	70	70	50	50	30	70	70	50	50	30	
Rf of Wall	50	30	50	30	30	50	30	50	30	30	
Rf of Floor	20	20	20	20	20	20	20	20	20	20	
Room dimensions		Viewed crosswise					Viewed endwise				
X	Y										
2H	2H	7.80	8.70	8.20	9.06	9.43	8.25	9.15	8.65	9.51	9.88
	3H	8.64	9.45	9.07	9.83	10.23	9.08	9.88	9.50	10.26	10.66
	4H	9.18	9.93	9.62	10.32	10.74	9.53	10.28	9.97	10.67	11.09
	6H	10.02	10.70	10.48	11.12	11.57	10.28	10.96	10.74	11.38	11.83
	8H	10.58	11.23	11.04	11.66	12.12	10.80	11.45	11.26	11.87	12.33
	12H	11.32	11.93	11.78	12.37	12.84	11.47	12.08	11.93	12.52	12.98
4H	2H	8.12	8.87	8.56	9.26	9.68	8.50	9.25	8.94	9.64	10.06
	3H	9.13	9.75	9.59	10.19	10.66	9.48	10.10	9.94	10.54	11.01
	4H	9.90	10.44	10.38	10.90	11.40	10.16	10.70	10.64	11.16	11.66
	6H	10.95	11.43	11.46	11.92	12.42	11.13	11.60	11.64	12.10	12.60
	8H	11.69	12.14	12.22	12.63	13.15	11.83	12.27	12.35	12.77	13.29
	12H	12.63	13.04	13.16	13.53	14.10	12.71	13.11	13.23	13.60	14.17
8H	4H	10.17	10.61	10.69	11.11	11.63	10.40	10.84	10.92	11.33	11.86
	6H	11.53	11.90	12.08	12.41	12.97	11.67	12.03	12.21	12.55	13.11
	8H	12.54	12.84	13.10	13.39	13.94	12.64	12.94	13.21	13.50	14.04
	12H	13.74	13.97	14.32	14.52	15.09	13.78	14.01	14.36	14.56	15.13
12H	4H	10.26	10.67	10.79	11.16	11.72	10.48	10.88	11.00	11.37	11.94
	6H	11.78	12.08	12.35	12.64	13.19	11.91	12.21	12.48	12.77	13.31
	8H	12.87	13.09	13.44	13.65	14.22	12.95	13.18	13.53	13.74	14.30
Variation with the observer position at spacings:											
S = 1.0H		1.2/-1.0					1.2/-1.0				
S = 1.5H		1.7/-1.1					1.7/-1.1				
S = 2.0H		2.2/-1.1					2.2/-1.1				
Standard tables:		BKBF					BKBF				
Uncorrected UGR		-3.5					-3.5				

依据CIE Publ. 117 □算 UGR, S/H = 0.25

no frame

no frame flex sm r e
no frame flex sm r cob série 2 e
no frame flex difusa sm r série 2 e
no frame flex sm r cob série 3 e



atenção

leia atentamente todas as instruções relacionadas ao seu produto antes de utilizá-lo.

antes de iniciar a instalação, certifique-se que a energia elétrica esteja desligada.

não são permitidas modificações no produto, esse deve atender à finalidade para a qual foi projetado e ser utilizado de acordo com as especificações técnicas.

em caso de dúvidas, entre em contato com o fabricante.

especificações técnicas

fonte de luz
módulo led integrado (incluso)

índice de proteção
IP20 - luminária para uso interno

peso
no frame flex sm r e - 0,4kg
no frame flex sm r série 2 cob - 0,4kg
no frame flex difusa sm r série 2 e - 0,4kg

cuidados com o produto
o produto deve ser manuseado com cuidado para evitar riscos e deformações.

para limpeza, utilize detergente neutro e um pano de algodão macio. finalize com um pano de algodão seco.

instalação

conteúdo da embalagem
1 luminária

ferramentas necessárias
chave philips


informações importantes
para a instalação, lave as mãos e seque as mãos, use luvas descartáveis.

antes de iniciar a instalação, certifique-se que a energia elétrica esteja desligada.


retire a luminária da embalagem com cuidado e apoie-o em uma superfície limpa e seca.

instalação passo a passo


1. faça um nicho no forro conforme a tabela abaixo:
no frame flex sm r e - nicho = Ø96
no frame flex sm r série 2 cob - nicho = Ø96
no frame flex difusa sm r série 2 e - nicho = Ø96




2. desmonte o módulo (mld1) retirando a grapa de fixação (gf1) e o corpo (co1).




3. encaixe o corpo (co1) no nicho.




4. passe as grapas de fixação (gf1) pelo centro do corpo (co1) conforme a imagem (a) e encaixe na fresta conforme a imagem (b) faceando o corpo com o gesso.




5. utilize os parafusos (p1) para fixar o chassi (ch1) e de o acabamento no forro com gesso, não deixando o parafuso aparente. espere a secagem do gesso para prosseguir a próxima etapa.



6. faça a ligação elétrica. isole os fios separadamente com fita isolante. repita a operação envolvendo o conjunto dos fios, vedando completamente a emenda.



7. encaixe o módulo (mld1) no corpo (co1).



8. a luminária após instalada deverá ficar como ilustrado na imagem. ligue a rede elétrica e teste o seu funcionamento.

