



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: darklight 34 c serie 2 fm

LampCAT: modulo led 12W 30K irc 90

Ballast type: led driver 700mA

Report No:

Voltage(V): 127.1100

Test No:

Current(A): 0.1140

Number of Lamps: 1

Power (W): 14.3390

Lamp flux(lm): 1460.0

PF: 0.9860

Length(mm): 320

Width(mm): 25

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 1302.47, Efficiency(%): 89.21% , Luminous Efficacy(lm/W): 90.83

Central intensity(cd): 3921.576, Maximum intensity(cd): 3921.576

Angle of maximum intensity: $C=0.0$ $\gamma=0.0$



Beam angle of C0 plane : 32.87

Aveage BeamAngle(IEC 61341):32.87


Equipment: equipamento lumini
Temperature(°C): 25.4

Date: 14/02/2025
Humidity(%): 66.0%


Operator: 01
Distance(m): 6.90



C0(Max):
C0/C180:
C90/C270:



Max , Ave Beam angle of C0 plane 32.87



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:5

Luminance Table


γ	45	50	55	60	65	70	75	80	85
C0	5085	3279	2010	1280	1190	1396	1842	2737	5463
C45	5085	3279	2010	1280	1190	1396	1842	2737	5463
C90	5085	3279	2010	1280	1190	1396	1842	2737	5463

L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
1190	1190	1190	1842	1842	1842	5463	5463	5463

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve



Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.4

Date: 14/02/2025
Humidity(%): 66.0%

Operator: 01
Distance(m): 6.90