



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: darklight 50 c serie 2 fa

LampCAT: modulo led 18W 30K irc 90

Ballast type: led driver 700mA

Report No:

Voltage(V): 127.0200

Test No:

Current(A): 0.1650

Number of Lamps: 1

Power (W): 20.7810

Lamp flux(lm): 2190.0

PF: 0.9890

Length(mm): 486

Width(mm): 25

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 1680.56, Efficiency(%): 76.74% , Luminous Efficacy(lm/W): 80.87

Central intensity(cd): 2020.568, Maximum intensity(cd): 2027.359

Angle of maximum intensity: C=0.0 γ =5.0



Beam angle of C0 plane : 53.16

Aveage BeamAngle(IEC 61341):53.16


Equipment: equipamento lumini
Temperature(°C): 25.4

Date: 14/02/2025
Humidity(%): 66.0%

Operator: 01
Distance(m): 6.90




C0(Max):
C0/C180:
C90/C270:



Max , Ave

Beam angle of C0 plane 53.16



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:5

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	15818	8326	3324	1243	832	951	1255	1862	3715
C45	15818	8326	3324	1243	832	951	1255	1862	3715
C90	15818	8326	3324	1243	832	951	1255	1862	3715


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
832	832	832	1255	1255	1255	3715	3715	3715

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 ———

C45 ———

C90 ———

Equipment: equipamento lumini
Temperature($^{\circ}$ C): 25.4

Date: 14/02/2025
Humidity(%): 66.0%

Operator: 01
Distance(m): 6.90