



lumini Solucoes em Iluminacao LTDA
www.lumini.com.br
Email:laboratorio@lumini.com.br
Tel:+55 11 3437-5555 Fax:+55 11 3437-5555
Address:Rua Ferreira Viana, 716 - Socorro - São Paulo/SP

lumini

LumCAT:

Luminaire: mini frame darklight 17 serie 3 e fa

LampCAT: modulo led 12W 30K irc 90

Ballast type: led driver 700mA

Report No:

Voltage(V): 127.0000

Test No:

Current(A): 0.1090

Number of Lamps: 1

Power (W): 13.5820

Lamp flux(lm): 1290.0

PF: 0.9850

Length(mm): 160

Width(mm): 25

Phm Type: C

Height(mm): 0

Photometric Results

Lumens(lm): 979.94, Efficiency(%): 75.96% , Luminous Efficacy(lm/W): 72.15

Central intensity(cd): 1261.046, Maximum intensity(cd): 1261.451

Angle of maximum intensity: C=0.0 γ =2.0


Beam angle of C0 plane : 50.83


Aveage BeamAngle(IEC 61341):50.83

Equipment: equipamento lumini
Temperature(°C): 26.3


Date: 12/02/2025
Humidity(%): 57.0%

Operator: 01
Distance(m): 6.90





Max , Ave Beam angle of C0 plane 50.83



lumini

Luminance Limiting Curve(no luminous side)

Appendix Page: 5 Total:5

Luminance Table

γ	45	50	55	60	65	70	75	80	85
C0	27128	14779	6057	2345	1486	1705	2225	3316	6623
C45	27128	14779	6057	2345	1486	1705	2225	3316	6623
C90	27128	14779	6057	2345	1486	1705	2225	3316	6623


L(Hor)(65)	L(Ver)(65)	L45(65)	L(Hor)(75)	L(Ver)(75)	L45(75)	L(Hor)(85)	L(Ver)(85)	L45(85)
1486	1486	1486	2225	2225	2225	6623	6623	6623

Glare Table

Glare	Quality	Service Values Illuminance(lx)							
1.15	A	2000	1000	500	≤ 300				
1.5	B		2000	1000	500	≤ 300			
1.85	C			2000	1000	500	≤ 300		
2.2	D				2000	1000	500	≤ 300	
2.55	E					2000	1000	500	≤ 300
		a	b	c	d	e	f	g	h

Luminance Limiting Curve

$\gamma(^{\circ})$



C0 ———

C45 ———

C90 ———

Equipment: equipamento lumini
Temperature($^{\circ}\text{C}$): 26.3

Date: 12/02/2025
Humidity(%): 57.0%

Operator: 01
Distance(m): 6.90